

Series BL

Model Number	Outline dimensions			Thread	Main dimensions (mm)										Static load kn	Weight (g)
	L	D	ℓ		L_2	L_3	D_2	D_3	W O -0.2	d	ℓ_2	d_2	Ball dia. ϕ	2θ		
BL-6	38	16	34	M6×1	16	5	10	13	11	8	16	7	11.11	40°	26	26
BL-8	46	19	41	M8×1.25	19	6	12.5	16	14	10.5	17	9	12.7	40°	50	49
BL-10F	56	25	52	M10×1.25	23	7	14.5	19	17	14	26	11	15.88	40°	75	90
BL-10	56	25	52	M10×1.5	23	7	14.5	19	17	14	26	11	15.88	40°	75	90
BL-12F	65	29	58	M12×1.25	26	8	17.5	22	19	16	29	13	19.05	40°	100	148
BL-12	65	29	58	M12×1.75	26	8	17.5	22	19	16	29	13	19.05	40°	100	148
BL-14F	74	34	75	M14×1.5	30	10	20	25	22	18	30	15	22.22	40°	120	245
BL-14	74	34	75	M14×2	30	10	20	25	22	18	30	15	22.22	40°	120	245
BL-16F	83	38	80	M16×1.5	34	11	22	27	24	19	32	17	22.22	30°	140	325
BL-16	83	38	80	M16×2	34	11	22	27	24	19	32	17	22.22	30°	140	325